



CoroChuck® 930

Mechanical locking
collet



Technical specifications



www.sandvik.coromant.com/corochuck930

Head office:
AB Sandvik Coromant
SE-811 81 Sandviken, Sweden
www.sandvik.coromant.com
E-mail: info.coromant@sandvik.com

92060
AB Sandvik Coromant
2019.02.01



Pull the shank and hold clockwise to stop while clamping.
N.B. use protection to prevent injury.



| Of application | Bore metric (inch) | | Accessories | |
|-------------------------|--------------------|------------|--------------|---------------|
| | DCON WS | DCON MS | Anchor screw | Assembly tool |
| CoroChuck 930 HD32 | 16 (5/8) | 32 (1.260) | 5519 140-02 | 5680 140-02 |
| | 20 (3/4) | | | |
| | 25 (1) | | | |
| CoroChuck 930 HD/S25 | 12 (1/2) | 25 (0.983) | 5519 140-02 | 5680 140-02 |
| | 16 (5/8) | | | |
| | 20 (3/4) | | | |
| CoroChuck 930 HD/S20 | 10 (3/8) | 20 (0.787) | 5519 140-01 | 5680 140-01 |
| | 12 (1/2) | | | |
| | 16 (5/8) | | | |

DCON WS = Connection diameter workpiece side

DCON MS = Connection diameter machine side